





Crimpeinstellungen

Crimp adjustment

contact no.	picture	tool	locator	wire diameter mm ²	locator position	tool adjustment mm
03-000001-01-20		T-9001	T-8001	0,14	5	0,78
				0,25	5	0,80
				0,34	5	0,85
				0,50	5	0,85
				0,75	5	0,90
				1,00	5	1,00
04-000001-01-20		T-9001	T-8001	0,14	5	0,78
				0,25	5	0,80
				0,34	5	0,85
				0,50	5	0,85
				0,75	5	0,90
				1,00	5	1,00
03-000002-01-20		T-9001	T-8001	0,35	2	1,05
				0,50	2	1,15
				0,75	2	1,25
				1,00	2	1,35
				1,50	2	1,55
				2,50	2	1,80
54-000002-01-00		T-9001	T-8001	0,35	4	1,05
				0,50	4	1,15
				0,75	4	1,25
				1,00	4	1,35
				1,50	4	1,55
				2,50	4	1,80

Technische Änderungen vorbehalten! / Technical deviation reserved!

Vor Verwendung der angegebenen Informationen und Daten, muss sich der Anwender über Aktualität und Gültigkeit dieser Ausfertigung rückversichern. Die Gültigkeit dieses Dokuments erlischt bei Gesetzgebungs- bzw.

Normenänderung. Etwaige Schutzrechte sowie bestehende Gesetze sind vom Anwender in eigener Verantwortung zu beachten.

Before using the information and data provided, the user have to re-insure the topicality and validity of this document. The validity of this document expires in the case of legislative changes and changes to standards. Any rights of protection as well as existing laws are to be observed by the user in his own responsibility.